

## **Universal testing machine**

HN-S Pro Series





Technology



The HM-S model, which is part of the Hoytom PRO series, can achieve nominal capacities between 100 and 250 kN. Its high quality load cells provide a high degree of test precision. It can also be equipped with an extensive range of fixtures, such as tensile grips, compression plates, bending fixtures, extensometers, etc.

Each machine includes HoyWin<sup>®</sup> test control software, and our custom designed electronics. This enables users to extract maximum performance and precision, through a simple and illustrative interface.

It is mainly geared for use in production, for repetitive testing with similar longitudinal specimens, etc.

## Characteristics:

- Extremely rigid frame for minimum deformation during testing.
- Robust preload precision ball screw.
- HBM<sup>®</sup> load cell (international leader in this technology).
- Computer, HoyWin<sup>®</sup> software and monitor (peripherals).
- Modern appearance with ergonomic design.
- Easy to transport via forklift or crane.

## Optional accessories:

- Manual, pneumatic or hydraulic grips.
- Large range of tools for each test.
- Extensometers.
- Perimeter guards.

Capacity kN	100-150	200-250
Maximum Speed	200	140
Travel	460	460
Maximum vertical space	900	900
Space between grips *1	475	460
Space between columns	620	620
Dimensions (W x D x H)	730 x 585 x 2070	730 x 585 x 2070
Weight	560	600
Power supply	220 V	
Power	750	1000

Force transducer		Displacement transducer	
Machine accuracy (Class) *2	0.5	Туре	Incremental encoder on servomotor
Range	0.4% – 100% FS	Resolution	< 0.001mm
Resolution	0.001% FS	Accuracy	<0.1%

<sup>\*1</sup> With grips type MO-CP, MO-CN or MO-CH.

\*2 According to Standards ISO 7500 and ASTM E4.







Hoytom es una marca registrada de Hoytom S.L. Hoytom se reserva el derecho a cambiar las especificaciones sin previo aviso



## **Die Maschine**



 $\mathcal{Y}$ 

 $\succ$ hoytom@hoytom.com 

youtube.com/hoytom